

Title Armchair

Date 1820-1840

Primary Maker Fanny Gaylord

Medium Maple, ash, splint

Basic Detail Report

Description Maple armchair with a slat-back, turned stiles and front legs, and a woven splint seat. The back of the armchair is formed by four horizontal slats between two cylindrical styles; each stile has an urn-shaped finial at the top. Each slat is curved back in the center and has an arched top edge. Below the seat, each stile forms a cylindrical back leg. Each arm is straight and has a scrolled handhold that extends well past the top of the front leg. The upper onethird of each front leg is turned with a baluster form; the remainder of the leg is cylindrical. Above the seat, each front leg supports the arm. The chair has a trapezoidal splint seat woven in a herringbone pattern. Each side of the chair has a turned stretcher below the arm and above the rush seat, that joints the upper portion of the front leg to the rear stile. These stretchers are each turned with a double-baluster form. The front and both sides of the chair each have two plain, cylindrical stretchers. The back has one plain, cylindrical stretcher. The frame is painted green. Condition: The frame has been re-glued. The top two slats are replaced; the top edge of the third slat is replaced. Each foot is replaced; an iron band circles the left front leg where the foot joins the leg. There is a hole where the round tenon at the top of each front leg extends up into the arm. There are multiple light scratches and gouges in the finish and the wood on the arms and the front legs. The green paint may be original; it is well worn on the arms and stretchers, but is not applied on the replaced parts. The splint seat is replaced. Design and Construction Details: The top and bottom slat are tenoned and pinned into each stile; the slats between are tenoned into each stile. The back of each arm is tenoned and pinned into the stile. The underside of

Basic Detail Report

each arm is straight toward the back, thicker where it joins the front leg, and notched just behind the scrolled handhold. Each front leg is tenoned and pinned into the handhold above. Each seat rail is probably bladelike, with a rounded outer edge and a tapered inner edge. The seat rails and stretchers are tenoned into the front or back legs and the stiles. Faint grooves circle the stiles and legs, marking the placement of the slats, seat rails, and stretchers.

Dimensions Primary Dimensions (overall height x width x depth): $43\ 1/8\ x\ 23\ x\ 16$ 3/4in. (109.5 x 58.4 x 42.5cm)