

Basic Detail Report



Title Side Chair

Date 1770-1780

Primary Maker Unknown

Medium Maple frame, tulip poplar splat, red watered moreen, linen

Basic Detail Report

Description Maple side chair in the Chippendale, or rococo, style, with a yoke-

shaped crest rail, a splat-back, straight front legs and stretchers, and an

upholstered slip seat. The back of the chair is formed by a crest rail atop two

stiles. The crest rail has a recessed center section with a small spur at each side;

to each side of center is an arched section that ends in a sharp ear where the

crest rail meets the stile. Centered below the crest rail is a solid, vase-shaped

splat, which attaches at the bottom to a rectangular stay rail immediately over

the back seat rail. Above the seat, each stile is slants backward slightly. Below

the seat, each stile forms a back leg that is slanted toward the center back of the

chair. The seat is trapezoidal, with an upholstered removable slip seat. The front

legs are straight and extend from the height of the feet down to form a plain

foot. All four sides of the chair have a plain, rectangular stretcher. Condition: The

frame has been re-glued. The red moreen on the slip seat is replaced; all other

upholstery materials are original. The finish is original and has been cleaned.

Design and Construction Details: Design. The top front edge of the stay rail has

cyma molding. The top edge of the side and front seat rails, and the top of each

leg, has ovolo molding. The exterior corner of each front leg, and the top exterior

edge of each front and side stretcher is molded with an ovolo flanked by a fillet.

Chair Frame. The crest rail is supported on a rectangular tenon at the top of each

stile and on a long rectangular tenon at the top of the splat. The back edges of

each stile, above the seat, are chamfered. The back side edges of the splat are

chamfered. The splat is tenoned into the back seat rail; the stay rail has a

rectangular cut out in the back to accommodate the shape of the splat, and is

Basic Detail Report

nailed down on top of the back seat rail. The back seat rail, each side seat rail, and the front seat rail are tenoned and pinned into the back or front legs. The interior top edge of the front and side seat rails, as well as the top of each front leg, has a rabbet to support the slip seat. Each stretcher is tenoned and pinned into the legs. The back exterior corner of each back leg is chamfered slightly. The front legs are more slender than the back legs. Tool marks are visible on the back of the frame. Upholstered Slip Seat. The upholstered slip seat consists of the present salmon, or red, watered moreen (replaced), over an undercover, stuffing, sackcloth, webbing, and a trapezoidal frame. The moreen is tacked to the frame with small iron nails (replaced). Larger, rose-headed iron nails remain in the underside of the frame.

Dimensions Primary Dimensions (overall height x width x depth): 37 1/8 x 21 1/4 x 19 1/4in. (94.3 x 54 x 48.9cm)