

Basic Detail Report



Title Side Chair

Date 1740-1760

Primary Maker General Andrew Ward V

Medium Maple, rush

Basic Detail Report

Description Maple side chair in the Queen Anne, or late baroque style, with a

yoke-shaped crest rail, a vase-shaped splat, turned front legs and front

stretcher, and a rush slip seat. The back of the chair is formed by a yoke-shaped

crest rail atop two stiles. The crest rail bows down in the center and has a deeply

beveled ridge at either side. Centered below the crest rail is a solid, vase-shaped

splat, which attaches at the bottom to the stay rail. The bottom front edge of the

stay rail is molded with a cyma curve, or S-curve. Each stile has a molded front,

consisting of a projecting semi-circle with a bead to either side; this molding

extends from the arched sides of the crest rail down to just above the level of the

seat. Above the seat, each stile curves backward. Below the seat, each stile

slants backward, over a foot that slants back even further. The rush seat is

trapezoidal in shape. The front and side rails each have a molded top surface,

consisting of a projecting semi-circle flanked by a bead. Each front corner of the

seat is supported by a block at the top of the front leg. The front skirt between

these blocks has a molded lower edge, consisting of a horizontal in the center

with a deep cyma curve to each side. Each front leg is turned with a sequence of

baluster, ring, block, baluster, ring, block, over a baluster-and-ring form foot.

The front stretcher connecting the two front legs is turned with double-ball-and-

ring forms. Both sides and the back each have one rectangular stretcher.

Condition: The rush is bowed down in the center of the seat and is painted

white; portions of the white paint at the front edge are loose. The splat has split

slightly in four locations at the front. A portion of the lower right side of the crest

rail and the top of the right stile have both split and been repaired with wooden

Basic Detail Report

pins or nails through the top. The chair had an upholstered slip seat at one time.

Design and Construction Details: The crest rail is supported by a tenon at the top of each stile; each of these joint is secured with a wooden pin. The splat is tenoned into the crest rail above and into the stay rail below. The stay rail and back seat rail are tenoned to each stile. Each side seat rail and the front skirt are tenoned and pinned into the stile or the front leg. The top surface of the rush slip seat has been painted white. The frame of the rush slip seat has a block at each corner. Each of the slip seat rails is blade-like, with a rounded outer edge and a tapered inner edge. The slip seat frame is held in place in the chair frame by trim strips, or strips of wood, at the top of the side seat rails, the front legs, and the front skirt. These strips of wood are molded and nailed in place. Additionally, a strip of wood is nailed to the interior back of the back seat rail; this also provides support for the seat. The side stretchers are tenoned and pinned into the front and back legs. The front stretcher is tenoned into the front legs. The back stretcher is tenoned into the back legs.

Dimensions Primary Dimensions (overall height x width x depth): 27 7/8 x 18 9/16 x 18 1/4in. (70.8 x 47.1 x 46.4cm)