

Basic Detail Report



Title Highchair

Date about 1770

Primary Maker Thomas Hart Hooker

Medium Maple, rush

Basic Detail Report

Description Highchair in the William and Mary, or early baroque, style, with a

slat-back, turned upper stiles, arms, front legs, and stretchers, and a rush seat.

The back of the chair is formed by three horizontal slats between two stiles;

each stile has a compressed ball and ring form finial at the top, over cylinder and

ring forms. Each slat curves back in the center and has an arched top edge; the

top slat has the steepest arch, which each succeeding slat becoming

progressively flatter. Below the seat, each stile forms a square back leg. Each

arm is straight and has a cylinder and ring form handhold that extends past the

top of the front leg. Each front leg is turned with baluster, cylinder, and ring

forms over a small, baluster-form foot. Above the seat, each front leg supports

the arm. The chair has a trapezoidal rush seat. The front of the chair has a foot

rest connecting the front legs. All four sides of the chair have a plain turned

stretcher. Condition: The foot rest may be a later replacement; it was

deliberately made from wood that had insect holes. The back of the left stile,

between and second and third slat, is gouged. The surface of the front legs, the

slats, and the upper portion of the stiles is well worn and lightly scratched. The

front feet and rush seat are replaced. Design and Construction Details: The top

slat is tenoned and pinned into the top of each stile; the slats below are tenoned

into each stile. Tool marks are visible on the front of the top and middle slat. The

back of each arm is tenoned into the stile. The top of each stile is turned, while

the leg below is square and roughly formed. Each front leg is tenoned and

pinned into the handhold above. The front end of each arm has a small

cylindrical hole; the hole on the right handhold is larger. Each seat rail is

Basic Detail Report

probably bladelike, with a rounded outer edge and a tapered inner edge. The

seat rails and stretchers are tenoned into the front and back legs. Each back

corner of the foot rest is tenoned and possibly nailed into the front leg. Faint

grooves circle the stiles and legs, marking the placement of the slats, seat rails,

and stretchers.

Dimensions Primary Dimensions (overall height x width x depth): $37 \frac{3}{8}$ x $16 \frac{3}{4}$

x $17 \frac{3}{4}$ in. (94.9 x 42.5 x 45.1cm)