

Basic Detail Report

Title Rocking Chair

Date 1690-1710

Primary Maker Richard Lord

Medium Beech primary wood, maple, ash, and oak secondary wood, cane, and splint

Description Beech rocking chair (originally an armchair) with a pierced and carved crest rail and front stretcher, a caned back panel and splint seat, and turned stiles, front legs, and stretchers in the William and Mary, or early baroque, style. The back of the chair is formed by a pierced and carved crest rail at the top between two stiles; each stile has a ball-and-urn finial at the top. The crest rail is carved with two tapered tiers of symmetrical arched leaves in the center, flanked by deep, carved scrolls. Below the crest rail are two vertical back supports with a panel of woven cane between them. Each back support has a molded front, and each attaches at the bottom to the stay rail. Above the seat, each stile angle backward and is turned with cone, baluster, ball, and ring forms. Below the seat, each stile forms a leg turned with cylinder and block forms, over a backward-slanting foot. Each arm (replaced) is short, with a flat top surface and a handhold that scrolls out toward the side of the chair. Each arm is supported by a plain turned arm support (later addition) that extends down to the side stretcher. Each front leg (the right one is replaced) is turned with three blocks, each separated by a baluster. The top of each front leg extends slightly higher than the woven splint seat (later addition), which is trapezoidal in shape;

Basic Detail Report

the splints cover the molded front and side seat rails. The front stretcher

connecting the front legs is pierced and carved, in a pattern similar to the crest

rail. Each side of the chair has one turned stretcher with a block in the middle.

The chair has a medial stretcher, connecting the two side stretchers at the block.

The chair has one back stretcher, turned with ball and ring forms. The bottom of

each foot has been altered to accommodate two rockers (later addition). The

chair has a red stain. Condition: The arms are replaced. The arm supports and

the rockers are later additions. At one time, the chair had arms supported by the

front legs; the front legs above the seat have since been cut off. Each leg has

been cut down. The right front leg is replaced. At one time, the seat was caned;

currently, the chair has a woven splint seat that covers the seat rails. Two splints

around the left side of the front seat rail are broken. A small area of cane on the

back of the chair is broken. The chair is refinished. Design and Construction

Details: Each end of the crest rail has a tenon that extends into the block at the

top of the stile. Each back support is tenoned into the crest rail above and into

the stay rail below. Each end of the stay rail has a rectangular tenon that extends

into the stile. The back seat rail is tenoned into the stiles. The front and side seat

rails are tenoned and pinned into the legs in the front and into the stiles at the

back. The front stretcher is tenoned and pinned into the front legs. The back

stretcher is tenoned into the back legs. Each side stretcher is tenoned and

pinned into the front and back legs. The medial stretcher is tenoned into the

block in the center of each side stretcher. Each arm is tenoned into the stile and

is supported on a round tenon at the top of the arm support; the bottom of the

Basic Detail Report

arm support is tenoned into the block in the center of each side stretcher. Each

rocker is formed by a single shaped board that fits into cut-outs on the bottom

of the legs, which have been shortened.

Dimensions Primary Dimensions (height x width x depth): $50 \frac{1}{8} \times 26 \frac{13}{16} \times 31 \frac{1}{4}$

in. (127.3 x 68.1 x 79.4cm)