

Basic Detail Report



Title Armchair

Date 1800-1815

Primary Maker Simeon Goodrich

Medium Mahogany, horsehair cloth, brass nails

Basic Detail Report

Description Mahogany armchair in the Federal, or early neoclassical, style, with

a flat crest rail, three banisters, tapered front legs, and horsehair over-the-rails

upholstery. The back of the chair is formed by a straight crest rail atop two stiles;

the stiles are raked, or angled together slightly, from top to bottom. Three

vertical banisters are evenly spaced below the crest rail. Each banister is pierced

and carved; the center of each banister splits in half and widens to a patera, or

ribbed oval. The banisters are joined at the bottom to a rectangular stay rail.

Above the seat, each stile is slanted backwards. Below the seat, each stile forms

a backward-curving leg that slants toward the center back of the chair. Each arm

is straight and extends forward from the stile about two-thirds of the depth of

the chair. The arm is supported at the front by a curved arm support that slopes

down and forward to the side rail, just behind the front leg. The seat is

trapezoidal, with black horsehair over-the-rails upholstery (replaced) that is

held in place with a swagged line of brass nails (replaced) on the front and side

seat rails. The tapered front legs extend from the height of the seat down to the

foot. The back and sides of the chair each have a stretcher connecting the lower

portion of the legs. A medial stretcher (replaced) connects the two side

stretchers. Condition: The front legs are lightly scratched and worn. The medial

stretcher is replaced. The upholstery and brass nails are replaced. Design and

Construction Details: Design. The top and bottom of each banister widens

slightly to a semi-circular form. The upper portion of the stile is only about half

the width of the back leg; the stile changes width just above the seat. The

horizontal and vertical elements of the back of the armchair, excluding the

Basic Detail Report

banisters, are outlined with cock beading. The front and outer side of each front leg is molded with two wide recessed flutes, with a thin line of cock beading to each side. Chair Frame. The crest rail is supported by a tenon at the top of each stile. Above the seat, the back of each stile is rounded. Each banister is tenoned into the crest rail above and into the stay rail below. The stay rail is tenoned into the stiles; the back of the stay rail is rounded. The back of each arm is screwed into the stile. The front of each arm is supported on a tenon at the top of the arm support. Each arm support is screwed into the side seat rail; the screws are inserted through the interior of the seat rails. Each seat rail is tenoned into the stiles and into the top of the legs. A diagonal brace reinforces each front interior corner of the seat frame; this may be dovetailed into the front and side stretchers. Each side stretcher and the back stretcher are tenoned into the lower portion of the legs. The medial stretcher is dovetailed to the side stretchers. Upholstery (replaced). The armchair is upholstered with over-the-rails black horsehair. The upholstery is held in place with a row of swagged brass nails along the front and side seat rails; the nails follow the original nailing pattern. Below the horsehair is stuffing, sackcloth, and canvas webbing that is tacked directly to the top of the seat rails. The horsehair is wrapped around the bottom of the front and side seat rails and is held in place with small nails.

Dimensions Primary Dimensions (overall height x width x depth): 35 5/8 x 21 1/2 x 19in. (90.5 x 54.6 x 48.3cm)